



1-095 Quarter-Turn Polyamide Pr20.1 L18



for cutout 20.1, length 18, Polyamide

Advantages

- Polyamide Quarter-turn double insulated.
- RH or LH application.
- Pre-assembling by DIRAK is advisable.
- A pre-assembled Quarter-turn can be installed in the cutout.
- Water and dust-tight according to IP65 DIN EN 60529 by using: sealing kit 209-9002
- Water and dust-tight according to IP67 by using: sealing kit 209-9001

Materials

- **Housing, insert and cam:** PA, black



Housing, PA

	Part Number	Housing length	Door-thickness	Version	Grounding type	Installation type
a)	200-9077.00-00000	18,0 mm	max. 8,0 mm	with Nut, PA		screw-on
a)	200-9003.00-00000	18,0 mm	max. 8,0 mm	with Nut, steel, zinc plated		screw-on
a)	200-9044.00-00000	18,0 mm	max. 8,0 mm	with Grounding nut, stainless steel	Grounding nut	screw-on
a)	200-9064.00-00000	18,0 mm	max. 8,0 mm	with Grounding nut (stainless steel), flat external seal, grounding clip	Grounding clip	screw-on

Insert with spring washer + screw

Part Number	Insert	Material	Surface
-------------	--------	----------	---------

b)	200-9155.00-00000	Square 7mm	PA	black
b)	200-9156.00-00000	Square 8mm	PA	black
b)	200-9158.00-00000	Triangular 8mm	PA	black
b)	200-9159.00-00000	Double bit 3mm pin	PA	black
b)	200-9160.00-00000	Double bit 5mm pin	PA	black
b)	200-9161.00-00000	Slotted 2x4mm	PA	black
b)	200-9173.00-00000	Wing knob	PA	black
b)	200-9184.00-00000	Crescent czech	PA	black
b)	200-9186.00-00000	Slotted recessed coinproof	PA	black

Cams PA, L45

	Part Number	H-dimension	Stop	Material	Surface
c)	200-5318.00-00000	18,0 mm	Yes	PA	black
c)	200-5320.00-00000	20,0 mm	Yes	PA	black
c)	200-5322.00-00000	22,0 mm	Yes	PA	black
c)	200-5325.00-00000	25,0 mm	Yes	PA	black
c)	200-5328.00-00000	28,0 mm	Yes	PA	black

Complementary products

c1) 1-102 **Cams L35/45 steel**

Assembly options

200-0002.00-00000 **Assembling cam with o-ring**

200-0001.00-00000 **Assembling cam without o-ring**

200-0019.00-00000 **Assembling cam 90° to handle without o-ring**

200-0033.00-00000 **Assembling cam 90° to handle with o-ring**

Function extension

d)-e) 209-9001.00-00000 **Sealing kit IP67 for 200-Quarter-Turns**

d)-e) 209-9002.00-00000 **Sealing kit IP65 for 200-Quarter-Turns**

