

## 1-100 Quarter-Turn Pr20.1 L18













for cutout 20.1, length 18

#### **Advantages**

- Quarter-turn, RH or LH application.
- The Quarter-turn consists of three basic components a) to a4), b) and c) which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled Quarter-turn can be installed through the cutout.
- Housings with extended bodies see product system 1-110.
- IP65 according to DIN EN 60529by: sealing kit 209-9002.00-00000.
- IP67 according to DIN EN 60529 by: sealing kit 209-9001.00-00000.

### **Materials**

- Housing: zinc die, chrome plated or black or PA, black
- Nuts: steel, zinc plated
- Grounding nut: zinc die, untreated
- Grounding clip: stainless steel

#### Remarks

- 1. Nut
- 2. Grounding nut
- 3. Grounding clip



## Quarter-turn housing Ø28

	Part Number	Housing length	Door-thickness	Grounding type	Material	Surface	Installation type
a)	200-9001.00-00000	18,0 mm	max. 8,0 mm		zinc die	chrome plated	screw-on
a)	200-9002.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	chrome plated	screw-on
a)	200-9062.00-00000	18,0 mm	max. 8,0 mm	Grounding clip	zinc die	chrome plated	screw-on
a)	200-9048.00-00000	18,0 mm	max. 8,0 mm		zinc die	black	screw-on
a)	200-9049.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	black	screw-on
a)	200-9063.00-00000	18,0 mm	max. 8,0 mm	Grounding clip	zinc die	black	screw-on
a)	200-9004.00-00000	18,0 mm	max. 8,0 mm	Grounding clip	PA	black	screw-on

### Quarter-turn housing Ø30x4

	Part Number	Housing length	Door-thickness	Grounding type	Material	Surface	Installation type
b)	200-9045.00-00000	18,0 mm	max. 8,0 mm		zinc die	chrome plated	screw-on
b)	200-9046.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	chrome plated	screw-on
b)	200-9054.00-00000	18,0 mm	max. 8,0 mm		zinc die	black	screw-on
b)	200-9055.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	black	screw-on

# Quarter-turn housing Ø32x6

	Part Number	Housing length	Door-thickness	Grounding type	Material	Surface	Installation type
c)	200-9005.00-00000	18,0 mm	max. 8,0 mm		zinc die	chrome plated	screw-on
c)	200-9006.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	chrome plated	screw-on
c)	200-9050.00-00000	18,0 mm	max. 8,0 mm		zinc die	black	screw-on
c)	200-9051.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	black	screw-on
c)	200-9007.00-00000	18,0 mm	max. 8,0 mm		PA	black	screw-on
c)	200-9008.00-00000	18,0 mm	max. 8,0 mm	Grounding clip	PA	black	screw-on

## Quarter-turn housing 30x6

	Part Number	Housing length	Door-thickness	Grounding type	Material	Surface	Installation type
d)	200-9009.00-00000	18,0 mm	max. 8,0 mm		zinc die	chrome plated	screw-on
d)	200-9010.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	chrome plated	screw-on
d)	200-9052.00-00000	18,0 mm	max. 8,0 mm		zinc die	black	screw-on
d)	200-9053.00-00000	18,0 mm	max. 8,0 mm	Grounding nut	zinc die	black	screw-on

# Blind housing Ø28x4

	Part Number	Housing length	Door-thickness	Material	Surface	Installation type
e)	235-9209.00-00000	18,0 mm	max. 8,0 mm	zinc die	black	screw-on

### Complementary products

f) 1-101 Inserts Pr20.1

1-115 Handle for Quarter-Turn

1-270 Dust Caps and Sealing Plug Pr20.1

- 1-275 Emergency Handle + Anti-Rotation Device Pr20.1
- 1-270.01 Finger Pull for Quarter-Turn Pr20.1
- 6-100 **Key**
- g) 1-102 Cams L35/45 steel
- g1) 1-260 Hooked Cam
- g1) 1-261 Cams with Ramp
- g1) 1-262 Cam variable

### Assembly options

200-0002.00-00000 Assembling cam with o-ring

 $200\text{-}0001.00\text{-}00000 \ \textbf{Assembling cam without o-ring}$ 

200-0019.00-00000 Assembling cam 90° to handle without o-ring

200-0033.00-00000 Assembling cam 90° to handle with o-ring

### Function extension

209-9001.00-00000 Sealing kit IP67 for 200-Quarter-Turns

209-9002.00-00000 Sealing kit IP65 for 200-Quarter-Turns

