

1-150 Quarter-Turn with L-Handle Pr20.1 L18



for cutout 20.1, length 18, with or without cylinder

Advantages

- Quarter-turn with L-handle.
- RH or LH application.
- Versions **without cylinder** are water- and dust-tight according to IP65 DIN EN 60529.
- Versions **with cylinder** are water- and dust-tight according to IP54 DIN EN 60529.
- The Quarter-Turn consists of two basic components which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled Quarter-Turn can be installed in the cutout.
- All lockable handles supplied with two keys.

Materials

- **L-handle:** PA, black with zinc die core or zinc die, chrome plated or black
- **Grounding nut:** zinc die, untreated
- **Cam:** steel, zinc plated



Quarter-Turn with L-handle, PA, black with zinc die core

	Part Number	Housing length	Door-thickness	Latching type	Grounding type	IP protection	Installation type
a)	200-9401.00-00000	18,0 mm	max. 8,0 mm		Grounding nut	IP65	screw-on
b)	200-9402.00-00000	18,0 mm	max. 8,0 mm	keyed alike DIRAK 1333	Grounding nut	IP54	screw-on
b)	500-9402.00-00000	18,0 mm	max. 8,0 mm	keyed alike DS200	Grounding nut	IP54	screw-on
b)	200-9403.00-00000	18,0 mm	max. 8,0 mm	keyed different	Grounding nut	IP54	screw-on
c)	200-9483.00-00000	18,0 mm	max. 8,0 mm	Push button	Grounding nut	IP65	screw-on

Quarter-turn with L-handle, zinc die, chrome plated

	Part Number	Housing length	Door-thickness	Latching type	Grounding type	IP protection	Installation type
a)	200-9419.00-00000	18,0 mm	max. 8,0 mm		Grounding nut	IP65	screw-on
b)	200-9420.00-00000	18,0 mm	max. 8,0 mm	keyed alike DIRAK 1333	Grounding nut	IP54	screw-on
b)	200-9437.00-00000	18,0 mm	max. 8,0 mm	keyed different	Grounding nut	IP54	screw-on
b)	500-9420.00-00000	18,0 mm	max. 8,0 mm	keyed alike DS200	Grounding nut	IP54	screw-on
b)	501-9420.00-00000	18,0 mm	max. 8,0 mm	PAGODA keyed alike	Grounding nut	IP54	screw-on
b)	501-9437.00-00000	18,0 mm	max. 8,0 mm	PAGODA keyed different	Grounding nut	IP54	screw-on

Quarter-turn with L-handle, zinc die, black

	Part Number	Housing length	Door-thickness	Latching type	Grounding type	IP protection	Installation type
a)	200-9427.00-00000	18,0 mm	max. 8,0 mm		Grounding nut	IP65	screw-on
b)	200-9428.00-00000	18,0 mm	max. 8,0 mm	keyed alike DIRAK 1333	Grounding nut	IP54	screw-on
b)	200-9438.00-00000	18,0 mm	max. 8,0 mm	keyed different	Grounding nut	IP54	screw-on
b)	500-9428.00-00000	18,0 mm	max. 8,0 mm	keyed alike DS200	Grounding nut	IP54	screw-on
b)	501-9428.00-00000	18,0 mm	max. 8,0 mm	PAGODA keyed alike	Grounding nut	IP65	screw-on
b)	501-9438.00-00000	18,0 mm	max. 8,0 mm	PAGODA keyed different	Grounding nut	IP54	screw-on

Complementary products

- d) 1-102 **Cams L35/45 steel**
- d) 1-262 **Cam variable**

Assembly options

- 200-0001.00-00000 **Assembling cam without o-ring**
- 200-0019.00-00000 **Assembling cam 90° to handle without o-ring**
- 200-0020.00-00000 **Assembling cam, LH door**

