

## 1-151 Quarter-Turn with L-Handle Pr20.1 L18



for cutout 20.1, length 18, with different inserts

### Advantages

- Quarter-turn with L-handle for inserts.
- RH or LH application.
- Water- and dust-tight according to IP65 DIN EN 60529.
- The radial spring loaded insert automatically locks the handle when the handle rotates back into the closed position.
- This Quarter-turn with L-handle consists of two basic components which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled Quarter-Turn can be installed in the cutout.

### Materials

- a)
- **L-handle:** PA, black with zinc die core
  - **Insert:** zinc die, chrome plated
- b)
- **Cam:** steel, zinc plated



## Quarter-Turn with L-handle, PA, black with zinc die core

	Part Number	Housing length	Door-thickness	Insert	Grounding type
a)	200-9429.00-00000	18,0 mm	max. 8,0 mm	Square 6mm	Grounding nut
b)	200-9431.00-00000	18,0 mm	max. 8,0 mm	Square 8mm	Grounding nut
c)	200-9432.00-00000	18,0 mm	max. 8,0 mm	Double bit 3mm pin	Grounding nut
d)	200-9433.00-00000	18,0 mm	max. 8,0 mm	Double bit 5mm pin	Grounding nut
e)	200-9435.00-00000	18,0 mm	max. 8,0 mm	Triangular 8mm	Grounding nut
f)	200-9436.00-00000	18,0 mm	max. 8,0 mm	Slotted 2x4mm	Grounding nut
g)	200-9475.00-00000	18,0 mm	max. 8,0 mm	Slotted recessed coinproof	Grounding nut

## **Complementary products**

6-100 **Key**

h) 1-102 **Cams L35/45 steel**

h) 1-262 **Cam variable**

## **Assembly options**

200-0001.00-00000 **Assembling cam without o-ring**

200-0019.00-00000 **Assembling cam 90° to handle without o-ring**

200-0020.00-00000 **Assembling cam, LH door**

