

5-150 Clip-on Sealing Profiles EPDM / NBR



Advantages

- The sealing part of these profiles is made of sponge rubber and the clamp area consists of soft rubber with a steel clip-on core.
- In an extrusion process the two materials are bonded to each other through vulcanization.
- **EPDM profiles are tested according to UL 157 and UL 50E.**
- The profiles made of NBR are oil resistant.

Materials

- **Clip-on profiles:** EPDM or NBR
- **Carrier:** Soft rubber
- **Sealing part:** Sponge rubber



Clip-on sealing profile

	Part Number	Material	Material 2	Colour	Width W	Height H	Clamping range	Packaging unit
a)	209-0201.00-00000	soft rubber, EPDM	sponge rubber, EPDM	black	11,0 mm	21,5 mm	1,5 - 3,0 mm	50,0 m
a)	209-0201.1A-00000	soft rubber, EPDM	sponge rubber, EPDM	black	11,0 mm	21,5 mm	0,8 - 2,0 mm	50,0 m
a)	209-2201.00-00000	soft rubber, NBR	sponge rubber, NBR	black	11,0 mm	21,5 mm	1,5 - 3,0 mm	50,0 m
a)	209-0240.00-00000	soft rubber, EPDM	sponge rubber, EPDM	black	11,0 mm	21,5 mm	3,0 - 4,0 mm	100,0 m
b)	209-0205.00-00000	soft rubber, EPDM	sponge rubber, EPDM	black	8,4 mm	15,6 mm	1,0 - 2,0 mm	50,0 m
b)	209-0246.00-00000	soft rubber, NBR	sponge rubber, NBR	black	8,4 mm	15,6 mm	1,0 - 2,0 mm	50,0 m

c)	209-0205.1A-00000	soft rubber, EPDM	sponge rubber, EPDM	black	8,0 mm	15,0 mm	0,8 - 1,5 mm	50,0 m
d)	209-0211.00-00000	soft rubber, EPDM	sponge rubber, EPDM	black	9,3 mm	21,0 mm	1,0 - 2,5 mm	50,0 m
e)	209-0220.00-00000	soft rubber, EPDM	sponge rubber, EPDM	black	13,0 mm	29,5 mm	1,0 - 2,5 mm	50,0 m

