

7-060 Swinghandle FS PrC



for cutout C, for flat rods, for profile-cylinder, stainless steel AISI 316

Advantages

- Swinghandle for application with rod latch system see product system 7-040 and cutout version PrC 50x25mm.
- Water- and dust-tight according to IP65 DIN EN 60529 within the sealed area.
- Detailed dimensions of the cutout PrC see product system 3-010.
- The padlock device with rectangular base is fitted from the rear and so held captive between doorskin and swinghandle body.
- This opening can be filled with a rectangular blanking plate.

Materials

- **Swinghandle, dish, bearing part, dust cover, blanking plate:** stainless steel AISI 316
- **Cap:** PA, black
- **Swinghandle shaft and padlock bolt:** stainless steel AISI 303



Swinghandle for profile-cylinder

	Part Number	Version	Padlock	Installation type
a)	207-9292.00-00000	without cylinder dustcover		screw-on
a)	207-9293.00-00000	with cylinder dustcover		screw-on
a1)	107-9286.00-00000	with cylinder dustcover	Yes	screw-on
a1)	107-9287.00-00000	without cylinder dustcover	Yes	screw-on

* Complementary products

- c) 2-140 **Profile-Cylinder**
- c) 7-069 **Profile-Cylinder**
- d) 7-040 **Rod Latch FS PrC**
- b) 207-2506.80-00000 **Blanking plate for opening**

