

7-103 Quarter-Turn with L-Handle Pr20.1 L18



for cutout 20.1, length 18, stainless steel AISI 316

Advantages

- Quarter-turn with L-handle.
- RH or LH application.
- Water- and dust-tight according to IP65 DIN EN 60529.
- The Quarter-Turn consists of two basic components which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled Quarter-Turn can be installed in the cutout.
- All lockable handles supplied with two keys.
- **Price and delivery time on request.**

Materials

- **L-handle:** completely stainless steel AISI 316, surface polished
- **Nut and cam:** stainless steel



Quarter-turn with L-Handle

	Part Number	Housing length	Latching type	Door-thickness	Material	Installation type
a)	200-9418.00-00000	18,0 mm		max. 8,0 mm	stainless steel	screw-on
a)	200-9485.00-00000	18,0 mm	keyed alike DIRAK 1333	max. 8,0 mm	stainless steel	screw-on
a)	200-9486.00-00000	18,0 mm	keyed different	max. 8,0 mm	stainless steel	screw-on

* Complementary products

- b) 1-102 Cams L35/45 steel
- b) 7-105 Cams L35/45 stainless steel
- b) 1-262 Cam variable

Assembly options

- c) 200-0001.00-00000 **Assembling cam without o-ring**
- c) 200-0019.00-00000 **Assembling cam 90° to handle without o-ring**
- c) 200-0020.00-00000 **Assembling cam, LH door**

